

Analogue Desktop Telephones

Baseline Pro CLI terminal



Delivering a host of user-friendly features the analogue Baseline Pro CLI telephone matches your telephony networking requirements both in reliability and durability.

The slim design with small foot print will fit perfectly for a wide range of business communication requirements.

At a glance

- > Easy to use
- > Speaker Phone
- > CLI
- > Message waiting lamp
- > Last number redial
- > Hold button
- > Yellow hold key for access to PBX transfer facilities



Features

Called number display	
Calling number display	
Callers list	80
Callers list key	
Direct memory keys	8
Earth recall	
Hands-free mode	
Hold	
Last number redial	
Line Power	
Listen-in	
Memory back-up	
Message waiting LED	
Optional desk stand	
Pause insertion	
Post-dialling DTMF	
Pulse dialling	
Ringer LED	
Ringing tone selection	
Speaker volume control	
Time & call duration	
Time-break recall	
Timer key	
Tone dialling	
Wall mounting	

Technical Data

Physical characteristics

- Size: 160 x 205 x 73 mm (w x d x h)
- Weight: BaseLine Pro CLI 700 g
- Colour: dark grey/charcoal

Packaging

- Box size: 220 x 240 x 66 (w x d x h)

Environmental conditions

- Temperature range:
 - rated -5° C to +45° C
 - transport -15° C to +55° C
- Relative humidity:
 - rated 10% to 90% RH
 - transport 5% to 95% RH

Operating conditions

- The BaseLine Pro CLI range is line powered
- Up to 2 sets can be connected to one PBX port for BaseLine Pro CLI. This is reduced to 1 if message waiting is enabled on the set
- Two types of message waiting indication are supported for BaseLine Pro CLI
 - polarity reversal, activation voltage 20..60V, deactivation <2V
 - high voltage, activation voltage 85..120V, deactivation <65V
- Calling line identification compliant with the following standards are supported:
 - ETSI EN 300 659-1 V1.3.1 (2001-01)
 - ETSI EN 300 659-2 V1.3.1 (2001-01)
 - ETSI EN 300 659-3 V1.3.1 (2001-01)
- Transmission settings and voice quality are in compliance with the European telecom requirement TBR38

Compatibility

- Operation is successfully verified on the SV9X00, SL1X00 and SIP@Net Server/iS3000 platforms

Compliance

- European Directives & Standards
 - EMC: 2014/30/EU
 - LVD: 2014/35/EU
 - RoHS: 2011/65/EU
 - WEEE: 2012/19/EU
 - EMC: EN55024: 2010 / EN55032: 2012
 - Safety: EN60950-1:2006 + Amendments*

* EN60950-1:2006+A11:2009 +A1:2010+A12:2011+A2:2013

Deliverables

The BaseLine Pro sets are supplied with:

- a line cord (3 m long with RJ11 plugs on both ends)
- a user guide
- a wall mounting bracket

EMEA (Europe, Middle East, Africa)
 NEC Enterprise Solutions
www.nec-enterprise.com

For further information please contact NEC EMEA or:

NEC Corporation (Thailand) Ltd. (Head Office)

3 Rajnakarn Building, 22nd fl. and 29th fl.
 South Sathorn Road, Yannawa, Sathorn, Bangkok 10120
<https://th.nec.com> Email: Necare@nec.co.th

